



OTR Tyres

Datasheet



B01N Tyre technical data

TYre Size	Star Rating	Load Index	TRA Code	TD	TT/TL	Standard Rim	Tire inflated dimension (mm)		Max Load (kg)	Inflation Pressure (bar)	Max Speed (km/h)
							Diameter±1.5%	Section width±.5%			
17.5R25	☆☆	182/167	E3/L3	28	TL	14.00/1.5	1348	445	8500/5450	5.75/4.35	10/50
	☆	176/153/157							7100/3650/4125	4.5/3.0/3.5	10/40/50
20.5R25	☆☆	193/177	E3/L3	31	TL	17.00/2.0	1492	520	11500/7300	5.75/4.5	10/50
	☆	186/161/168							9500/4625/5600	4.5/3.75/3.5	10/40/50
23.5R25	☆☆	201/185	E3/L3	34	TL	19.50/2.5	1617	597	14500/9250	6.5/5.25	10/50
	☆	195/176							12150/7100	5.0/3.75	
26.5R25	☆☆	209/193	E3/L3	37	TL	22.00/3.0	1750	673	18500/11500	5.75/4.5	10/50
	☆	202/184							15000/9000	4.5/3.5	

Application

Designed for loaders, earthmovers and the equipment used in construction stockpile and for truck loading applications

Performance

- Excellent traction and stability.
- Deliver exceptional operator comfort