



OTR Tyres

Datasheet



B02N Tyre technical data

Tyre Size	Star Rating	Load Index	TRA Code	TD	TT/TL	Standard Rim	Tire inflated dimension (mm)		Max Load (kg)	Inflation Pressure (bar)	Max Speed (km/h)
							Diameter \pm 1.5 %	Section width \pm .5%			
23.5R25	☆☆	201/185	E3/L3	34	TL	19.50/2.5	1617	597	14500/9250	6.5/5.25	10/50
	☆	195/176							12150/7100	5.0/3.75	
26.5R25	☆☆	209/193	E3/L3	37	TL	22.00/3.0	1750	673	18500/11500	5.75/4.5	10/50
	☆	202/184							15000/9000	4.5/3.5	
29.5R25	☆☆	216/200	E3/L3	43,5	TL	25.00/3.5	1873	750	22400/14000	5.75/4.5	10/50
	☆	208/191							18000/10900 0	4.5/3.5	
29.5R29	☆☆	218/202	E3/L3	43,5	TL	25.00/3.5	1975	750	23600/15000	5.75/4.5	10/50
	☆	211/193							19500/11500	4.5/3.5	

Application

Applied for articulated Trucks

Performance

- With wide and stabile tread
- Excellent traction and adhesion
- Designed to deliver exceptional operator comfort