



OTR Tyres

Datasheet



BXDN Tyre technical data

Tyre Size	Star Rating	Load Index	TRA Code	TD	TT/TL	Standard Rim	Tire inflated dimension (mm)		Max Load (kg)	Inflation Pressure (bar)	Max Speed (km/h)
							Diameter \pm 1.5 %	Section width \pm .5%			
17.5R25	☆☆	182/167	E3/L3	28	TL	14.00/1.5	1348	445	8500/5450	5.75/435	10/50
	☆	176/153/157							7100/3650/4125	4.5/3.0/3.5	10/40/50
20.5R25	☆☆	193/177	E3/L3	31	TL	17.00/2.0	1492	520	11500/7300	5.75/4.5	10/50
	☆	186/161/168							9500/4625/5600	4.5/3.75/3.5	10/40/50
23.5R25	☆☆	201/185	E3/L3	34	TL	19.50/2.5	1617	597	14500/9250	6.5/5.25	10/50
	☆	195/176							12150/7100	5.0/3.75	
26.5R25	☆☆	209/193	E3/L3	37	TL	22.00/3.0	1750	673	18500/11500	5.75/4.5	10/50
	☆	202/184							15000/9000	4.5/3.5	
29.5R25	☆☆	216/200	E3/L3	37	TL	25.00/3.5	1873	750	22400/14000	5.75/4.5	10/50
	☆	208/191							18000/10900	4.5/3.5	

Application

Suitable for earthmovers and loaders

Performance

- Special tread depth
- Good traction in wet and muddy road
- Special tread design guaranteed the integral beauty