



Radial Tyres

Datasheet



DR909 Tyre technical data

Tyre Size	Ply	Load index		Speed Symbol	TD	TT/TL	Standard Rim	Alternation Rim	Tyre Inflated Dimension (mm)		Max Load (kg)		Inflation Pressure (bar)		Approvals
		Single	Dual						Diameter± 1.5%	Section width±.5%	Single	Dual	Single	Dual	
11R22.5	14	144	142	M	15	TL	8.25	7.50	1054	279	2800	2650	7,2	7,2	DOT,E
	16	148	145	M		TL					3150	2900	8,4	8,4	DOT,E,S
11R24.5	14	146	143	M	15	TL	8.25	7.50	1104	279	3000	2725	7,2	7,2	DOT,E
	16	149	146	M		TL					3250	3000	8,3	8,3	DOT,E
12R22.5	16	152	148	L	15,5	TL	9.00	8.25	1085	300	3550	3150	8,4	8,4	DOT,E,S
295/75R22.5	14	144	141	M	15	TL	9.00	8.25	1014	298	2800	2575	7,6	7,6	DOT,E
	16	146	143	M		TL					3000	2725	8,3	8,3	
285/75R24.5	14	144	141	M	15	TL	8.25	--	1050	283	2800	2575	7,6	7,6	DOT,E
	16	147	144	M		TL					3075	2800	8,3	8,3	DOT,E
295/80R22.5	16	152	148	M	15,5	TL	9.00	--	1044	298	3550	3150	8,3	8,3	DOT,E,S
315/80R22.5	18	154	151	M	17	TL	9.00	9.75	1076	312	3750	3450	8,3	8,3	DOT,E,S
	20	156	151	M		TL					4000	3450	8,5	8,5	DOT,E,S

Application

Apply for highway and normal roads.

For all bus applications and truck steering tyres.

Performance

- 4-rip main grooves with it's unique zig-zag pattern on sides assure the excellent traction and braking force, good water evacuation improves stability.
- Special tread groove design enables optimal self-cleaning
- Variable pitch design offers low noise characteristics
- Wide pattern grooves on shoulder with low heating compound realizes high-speed and durability performance.

Data/Information given above, are subject to change without notice

ICB-Germany, Talstr. 24, 97996 Niederstetten, Germany, e-mail: info@icb-germany.com